SPOT DESIGN

ELECTRIC CONVECTOR HEATER





BASIC AND COMPACT



SPOT DESIGN

Technical specifications

The efficient and compact base heating

Convector-specific compactness with ultra-reactive heat diffusion for enveloping warmth in the room.



SINGLE-BLOCK ALUMINUM HEATING TRANSMITER

- · The monobloc and monometal aluminum transmitter provides a very fast heating and perfect reactivity.
- · Its optimized «X» shape has been specially studied to create gentle heating by natural convection.


ENERGY SAVING OPTIONS

- · Open window detection.
- · Control locking.
- · Temperature calibration.
- · Integrated daily and weekly programming: 3 pre-set programmes.
- · On/off switch.



HORIZONTAL MODELS

1,5m power cord with EU plug





for mobile use (optional)

Power	Width	Heigth	Depth*	weight	Smooth white
Watts	mm	mm	mm	kg	Reference
500	340	440	104	2,8	E176111
1000	420	440	104	3,4	E176113
1500	580	440	104	4,5	E176115
2000	740	440	104	5,7	E176117
2500	900	440	104	7,1	E176118
Castor kit (optional)					A691600

Classe II

IP 24 IK 08

MADE IN FRANCE

^{*} Depth: when wall-mounted, including self-gauging H bracket